

Air Trolley

A hose cart provides a flexible connection from the fixed line to the place of application for breathing air. It takes care of order, protects the couplings from dust and dirt and prevents effectively hose tangles.

The basic model is the hose reel for fixed installation.

Available options:

- with 4 wheels, steerable and lockable
- with swiveling suspension for wall mounting
- with closed hood and stripping brushes

Properties:

- with connection (standard): Pedi safety couplings
 Supply line: Type M
 Output: Type W
 (other types of couplings on request).
- Supply line (standard): Length 2 m
- Air tubing:
 Inner diameter 13 mm
 approved acc. to DIN EN 139, antistatic
 highly flexible, min. bending radius 40 mm
- smooth surface, easy to decontaminate
- max. operating pressure: max. 10 bar



Available versions:

Item No. (Hard-mounted)	Hose length	Return system	Option Wheels, steering/stop	Option Suspension, swiveling	Option Hood with scraper brushes
115769	10 m	Spring	115773	113951	115775
115770	15 m	Spring	115773	113951	115775
115771	20 m	Spring	115773	113951	115775
115497	30 m	Crank	Wheels included	---	Protective cover included
111442	50 m	Crank	Wheels included	---	Protective cover included

Other versions (connection, supply lines, etc.) on request.